

Rotule SA GAR15-UK-DURBAL - GAR15-UK-DURBAL

https://www.123roulement.be/roulement-palier/rotule/sa/gar15-uk-durbal


GAR15-UK



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	B	C1	d2
GAR 15 UK	15	M 14	12	10,0	40

type	l, min	measurement [mm]	h	α [°]	load rating C ₀ [kN]	weight [kg]
GAR / GAL 15 UK	34	20	63	8	36,0	0,140

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952492933
Diam. intérieur	15 mm
Diam. intérieur	0.591" inch
Diam. extérieur	40 mm
Diam. extérieur	1.575" inch
Epaisseur	12 mm
Epaisseur	0.472" inch
Type	SA
Poids	140 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE