

# Rotule SA GAR20-UK-2RS-DURBAL - GAR20-UK-2RS-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/gar20-uk-2rs-durbal>


## GAR20-UK-2RS



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	d	G	B	C1	d2
right-hand thread GAR 20 UK (-2RS)	20	M 20 x 1,5	16	13,0	53

type	l1, min	measurement [mm] l2, min	h	alpha [°]	load rating C0 [kN]	weight [kg]
GAR / GAL 20 UK-2RS	43	27	78	9	60,0	0,310

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493060
Diam. intérieur	20 mm
Diam. extérieur	53 mm
Épaisseur	16 mm
Type	SA
Poids	310 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE