

Rotule SA GAR80-UK-2RS-DURBAL - GAR80-UK-2RS-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/gar80-uk-2rs-durbal>


GAR80-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	B	C1	d2
GAR 80 UK-2RS	80	M 64 x 4	55	47,0	180

type	l1, min	l2, min	h	α [°]	load rating C ₀ [kN]	weight [kg]
GAR / GAL 80 UK-2RS	140	100	270	6	750,0	12,000

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493541
Diam. intérieur	80 mm
Diam. extérieur	180 mm
Épaisseur	55 mm
Type	SA
Poids	12000 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE