

Rotule SI GIL6-UK-DURBAL - GIL6-UK-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/gil6-uk-durbal>

GIL6-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
GIL 6 UK			d	G	B	C ₁	C ₂	d ₂	d ₄
			6	M 6	6	4,4	21	10,0	13

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIL 6 UK	11	30	11	13	8,2	0,021

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493589
Diam. intérieur	6 mm
Diam. intérieur	0.236" inch
Diam. extérieur	21 mm
Diam. extérieur	0.827" inch
Epaisseur	6 mm
Epaisseur	0.236" inch
Type	SI
Poids	21 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE