


Rotule SI
GIR12-UK-DURBAL - GIR12-UK-DURBAL
<https://www.123roulement.be/roulement-palier/rotule/si/gir12-uk-durbal>

GIR12-UK

female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq 35$ with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq 17$ additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₄	
GIR 12 UK		12	M 12	10	8,0	34	17,5 22	

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIR 12 UK	23	50	19	11	24,5	0,096

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493695
Diam. intérieur	12 mm
Diam. extérieur	34 mm
Epaisseur	10 mm
Type	SI
Poids	96 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.be
02 808 18 02
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE