

Rotule SI

GIL15-UK-DURBAL - GIL15-UK-DURBAL

https://www.123roulement.be/roulement-palier/rotule/si/gil15-uk-durbal

GIL15-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	B	C ₁	d ₂	d ₄
GIL 15 UK	15	M 14	12	10,0	40	21,0 26

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 15 UK	30	61	22	8	36,0	0,180

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493732
Diam. intérieur	15 mm
Diam. extérieur	40 mm
Epaisseur	12 mm
Type	SI
Poids	180 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE