

Rotule SI

GIL17-UK-2RS-DURBAL - GIL17-UK-2RS-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/gil17-uk-2rs-durbal>

GIL17-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]			
right hand thread	left hand thread			C ₁	C ₂	d ₂	d ₄
GIL 17 UK (-2RS)	17	M 16	14	11,0	46	24,0	30

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 17 UK	34	67	27	10	45,0	0,220

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493770
Diam. intérieur	17 mm
Diam. extérieur	46 mm
Épaisseur	14 mm
Type	SI
Poids	220 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE