

Rotule SI

GIR20-UK-2RS-DURBAL - GIR20-UK-2RS-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/gir20-uk-2rs-durbal>

GIR20-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq 35$ with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq 35$ with additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	d	G	B	C ₁	C ₂	d ₂	d ₄
GIR 20 UK (-2RS)	20	M 20 x 1,5	16	13,0	53	27,5	35

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIL 20 UK	40	77	32	9	60,0	0,350

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493855
Diam. intérieur	20 mm
Diam. extérieur	53 mm
Épaisseur	16 mm
Type	SI
Poids	350 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE