

# Rotule SI

## GIR35-UK-2RS-DURBAL - GIR35-UK-2RS-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/gir35-uk-2rs-durbal>

### GIR35-UK-2RS



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq 35$  with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq 17$  additional seal on both sides upon request.

**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE fabric

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
no lubrication necessary,  
maintenance free



order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	C <sub>2</sub>	d <sub>2</sub>	d <sub>4</sub>
GIR 35 UK-2RS		35	M 36 x 3	25	21,0	82	47,0	58
type	measurement [mm]			α	load rating	weight		
GIR / GIL 35 UK-2RS	t <sub>3</sub> min	h	W	°	C <sub>0</sub> (kN)	[kg]		
	60	125	50	6	146,0	1,300		

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952494081
Diam. intérieur	35 mm
Diam. extérieur	82 mm
Épaisseur	25 mm
Type	-
Poids	1300 g
Filetage	-
Lubrification	-
Conditionnement	-

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE