


Rotule SI
GIL35-UK-2RS-DURBAL - GIL35-UK-2RS-DURBAL
<https://www.123roulement.be/roulement-palier/rotule/si/gil35-uk-2rs-durbal>

GIL35-UK-2RS

female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq 35$ with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq 17$ additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary, maintenance free

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₄
GIL 35 UK-2RS		35	M 36 x 3	25	21,0	82	47,0 58

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIL 35 UK-2RS	60	125	50	6	146,0	1,300

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952494098
Diam. intérieur	35 mm
Diam. extérieur	82 mm
Epaisseur	25 mm
Type	-
Poids	1300 g
Filetage	-
Lubrification	-
Conditionnement	-

contact@123roulement.be
02 808 18 02
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE