

Rotule SI

SIZPL12-S-DURBAL - SIPL12-S-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/sizpl12-s-durbal>

SIZPL12-S



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches

order number

right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SIZPL 12 S		12,70	1/2 - 20	15,88	12,70	33,32	18,67	22,23

measurement [mm]

type	inches	l ₁ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SIPL / SIPL 12 S	1 / 2 "	30,15	19,05	53,98	9	19,0	0,133

Diagram: Shows cross-sections of the rod end with dimensions labeled: B, C₁, d, G, W, d₂, d₃, d₄.

Material and Lubrication:
Rod end body: surface zinc plated
Sliding combination: steel / heavy duty bronze
Inner ring: bearing steel, hardened, ground and spherical surface chromium plated
Outer ring: heavy duty bronze with lubrication
Lubrication: lubrication required, with grease nipple

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952495811
Diam. intérieur	12.7 mm
Diam. intérieur	1/2" inch
Diam. extérieur	33.32 mm
Diam. extérieur	1.312" inch
Epaisseur	15.88 mm
Epaisseur	5/8" inch
Type	SI
Poids	133 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE