

Rotule SI SI17-ES-DURBAL - SI17-ES-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/si17-es-durbal>

SI17-ES



female thread; lubrication required, according to DIN ISO 12240-4; serie E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSL...ES-2RS with additional seals also available.

Rod end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

| order number | | measurement [mm] | |
|-------------------|------------------|------------------|------|
| right hand thread | left hand thread | d | G |
| SI 17 ES | | 17 | M 16 |

| type | measurement [mm] | | | | load rating C_0 [kN] | weight [kg] |
|--------------|------------------|----|----|--------------|------------------------|-------------|
| | l_1 min | W | h | α [°] | | |
| SI / SI17 ES | 34 | 27 | 67 | 10 | 45,0 | 0,22 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3663952496986 |
| Diam. intérieur | 17 mm |
| Diam. extérieur | 46 mm |
| Épaisseur | 14 mm |
| Type | SI |
| Poids | 220 g |
| Filetage | Filetage à droite |
| Lubrification | avec |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE