

# Rotule SI

## SI35-ES-2RS-DURBAL - SI35-ES-2RS-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/si35-es-2rs-durbal>

### SI35-ES-2RS



**female thread;**  
**lubrication**  
**required,**  
**according to**  
**DIN ISO 12240-4;**  
**serie E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSL...ES-2RS with additional seals also available.


**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required



order number	right hand thread	left hand thread	measurement (mm)						
SI 35 ES (-2RS)			d	G	B	C1	d2	d3	d4
			35	M 36 x 3	25	21,0	82	47,0	58

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	W	h	α [°]		
SI / SIL 35 ES (-2RS)	60	50	125	6	146,0	1,3

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497358
Diam. intérieur	35 mm
Diam. extérieur	82 mm
Épaisseur	25 mm
Type	SI
Poids	1300 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE