

Rotule SI

SIL45-ES-2RS-DURBAL - SIL45-ES-2RS-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/sil45-es-2rs-durbal>

SIL45-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; serie E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSL...ES-2RS with additional seals also available.

Rod end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SIL 45 ES (-2RS)			45	M 42 x 3	32	27,0	102	58,0	70

type	l1 min	W	h	alpha [°]	load rating C0 (kN)	weight (kg)
SI / SIL 45 ES (-2RS)	65	60	145	7	240,0	2,5

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497464
Diam. intérieur	45 mm
Diam. extérieur	102 mm
Epaisseur	32 mm
Type	SI
Poids	2500 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE