

## Rotule SI SI50-ES-DURBAL - SI50-ES-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/si50-es-durbal>

### SI50-ES



**female thread; lubrication required, according to DIN ISO 12240-4; serie E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSL...ES-2RS with additional seals also available.

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

**order number**

right hand thread	left hand thread	measurement (mm)						
d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>		
SI 50 ES		50	M 45 x 3	35	30,0	112	62,0	75

**measurement [mm]**

type	l <sub>1</sub> min	W	h	$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
SI / SI L 50 ES	68	65	160	6	290,0	3,5

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497556
Diam. intérieur	50 mm
Diam. extérieur	112 mm
Epaisseur	35 mm
Type	SI
Poids	3500 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE