

Rotule SI

SI80-ES-2RS-DURBAL - SI80-ES-2RS-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/si80-es-2rs-durbal>

SI80-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSL...ES-2RS with additional seals also available.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 80 ES (-2RS)			80	M 64 x 4	55	47,0	180	95,0	110

type	measurement [mm]				load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h	α [°]		
SI / SIL 80 ES (-2RS)	85	100	230	6	750,0	12,0

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497785
Diam. intérieur	80 mm
Diam. extérieur	180 mm
Epaisseur	55 mm
Type	SI
Poids	12000 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE