

Rotule SI

SIL80-ES-DURBAL - SIL80-ES-DURBAL

https://www.123roulement.be/roulement-palier/rotule/si/sil80-es-durbal

SIL80-ES



female thread; lubrication required, according to DIN ISO 12240-4; serie E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSL...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number

right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
	SIL 80 ES	80	M 64 x 4	55	47,0	180	95,0	110

measurement [mm]

type	l ₃ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SI / SIL 80 ES	85	100	230	6	750,0	12,0

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497822
Diam. intérieur	80 mm
Diam. extérieur	180 mm
Epaisseur	55 mm
Type	SI
Poids	12000 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE