

Rotule SA SAL12-E-DURBAL - SAL12-E-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/sal12-e-durbal>

SAL12-E



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
	SAL 12 E	12	M 12	10	8,0	34	

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 12 E	28	17	54	11	24,5	0,085	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497983
Diam. intérieur	12 mm
Diam. extérieur	34 mm
Epaisseur	10 mm
Type	SA
Poids	86 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE