

Rotule SA SA70-ES-2RS-DURBAL - SA70-ES-2RS-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/sa70-es-2rs-durbal>

SA70-ES-2RS



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Rad end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 70 ES (-2RS)		70	M 56 x 4	49	42,0	160

type	measurement [mm]			n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h			
SA / SAL 70 ES (-2RS)	125	80	235	6	610,0	8,200

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952498829
Diam. intérieur	70 mm
Diam. intérieur	2.756" inch
Diam. extérieur	160 mm
Diam. extérieur	6.299" inch
Epaisseur	49 mm
Epaisseur	1.929" inch
Type	SA
Poids	8200 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE