


Rotule TAPR GIHO-KL-20DO-DURBAL - GIHO-KL-20DO-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/tapr/giho-kl-20do-durbal>

GIHO-KL-20DO

Female thread:
hydraulic rod ends,
according to
DIN 24555



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required



* without grease nipple

order number	measurement [mm]									
right hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂	C ₃
GIHO-KL 20 DO*	20	24,1	55	M 14 x 1,5	25	55	16	13	17	

type	measurement [mm]				α	load rating	weight
	h ₁	l ₁	l ₂	l ₃	[°]	C ₀ [N]	[kg]
GIHO-K / GIHO-KL 20 DO	58	19	85,5	25	9	42,5	0,43

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500690
Diam. intérieur	20 mm
Diam. extérieur	55 mm
Epaisseur	13 mm
Type	TAPR
Poids	430 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE