


Rotule TAPR GIHO-K-30DO-DURBAL - GIHO-K-30DO-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/tapr/giho-k-30do-durbal>

GIHO-K-30DO

female thread:
hydraulic rod ends,
according to
DIN 24555




Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required



* without grease nipple

order number	measurement [mm]	
	right hand thread	left hand thread
GIHO-K 30 DO	30	34,2

type	measurement [mm]				α [°]	load rating C_0 [kN]	weight [kg]
	h_1	l_1	l_2	l_3			
GIHO-K / GIHO-KL 30 DO	85	29	125,0	35	6	108,0	1,25

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500768
Diam. intérieur	30 mm
Diam. extérieur	80 mm
Epaisseur	19 mm
Type	TAPR
Poids	1250 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE