


Rotule TAPR GIHO-KL-30DO-DURBAL - DGIHO-KL-30DO-DURBAL


<https://www.123roulement.be/roulement-palier/rotule/tapr/dgiho-kl-30do-durbal>


GIHO-KL-30DO

Female thread:
hydraulic rod ends,
according to
DIN 24555



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.





* without grease nipple

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂	
GIHO-KL 30 DO		30	34,2	80	M 20 x 1,5	36	77	22	19	19	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 30 DO	85	29	125,0	35	6	108,0	1,25

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500775
Diam. intérieur	30 mm
Diam. extérieur	80 mm
Epaisseur	19 mm
Type	TAPR
Poids	1250 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE