


## Rotule TAPR GIHO-KL-40DO-DURBAL - GIHO-KL-40DO-DURBAL


<https://www.123roulement.be/roulement-palier/rotule/tapr/giho-kl-40do-durbal>


### GIHO-KL-40DO

**Female thread:**  
hydraulic rod ends,  
according to  
DIN 24555



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.





\* without grease nipple

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

order number	measurement [mm]									
right hand thread	d	d <sub>1</sub>	d <sub>2</sub>	G	d <sub>4</sub>	d <sub>5</sub>	B	C <sub>1</sub>	C <sub>2</sub>	C <sub>3</sub>
GIHQ-KL 40 DO	40	45,0	100	M 27 x 2	45	90	28	23	23	

type	measurement [mm]				α [°]	load rating C <sub>0</sub> [N]	weight [kg]
	h <sub>1</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>			
GIHQ-K / GIHQ-KL 40 DO	105	37	155,0	45	7	156,0	2,16

### CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500805
Diam. intérieur	40 mm
Diam. extérieur	100 mm
Epaisseur	23 mm
Type	TAPR
Poids	2160 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE