

Rotule GEG GE12-LO-DURBAL - GE12-LO-DURBAL


<https://www.123roulement.be/roulement-palier/rotule/geg/ge12-lo-durbal>

GE12-LO



Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

Outer ring: bearing steel, hardened, ground and phosphated, single split in axial direction

Lubrication: lubrication required

| order number | measurement [mm] | | | | |
|--------------|------------------|----|---|--------------------|----|
| GE 12 LO | d | B | C | d ₁ min | D |
| | 12 | 12 | 7 | 15,5 | 22 |

| type | measurement [mm] | | | d ₁ | r ₁ | load rating C ₁₀ [N] | weight [kg] |
|----------|---------------------|---------------------|----------------|----------------|----------------|---------------------------------|-------------|
| | r ₁₅ min | r ₂₅ min | d ₂ | | | | |
| GE 12 LO | 0,3 | 0,3 | 18,0 | 4 | 53 | 0,022 | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | DURBAL |
| N° Ean13 | 3663952506364 |
| Diam. intérieur | 12 mm |
| Diam. extérieur | 22 mm |
| Epaisseur | 7 mm |
| Type | GEG |
| Poids | 22 g |
| Lubrification | avec |
| Conditionnement | - |
| Norme | Sans norme |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE