

Rotule GEG GE25-LO-DURBAL - GE25-LO-DURBAL


<https://www.123roulement.be/roulement-palier/rotule/geg/ge25-lo-durbal>

GE25-LO



Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

Outer ring:
bearing steel, hardened, ground and phosphated, single split in axial direction

Lubrication:
lubrication required

order number	measurement [mm]				
GE 25 LO	d	B	C	d ₁ min	D
	25	25	16	30,0	42

type	measurement [mm]			d ₂	r ₁ (r ₂)	load rating C ₁₀ (C ₉₀)	weight [kg]
	r ₁ min	r ₂ min	d ₁				
GE 25 LO	0,6	0,6	35,5	4	240	0,120	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952506401
Diam. intérieur	25 mm
Diam. intérieur	0.984" inch
Diam. extérieur	42 mm
Diam. extérieur	1.654" inch
Epaisseur	16 mm
Epaisseur	0.63" inch
Type	GEG
Poids	120 g
Lubrification	avec
Conditionnement	-
Norme	Sans norme

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE