

## Rotule GEG GE25-LO-DURBAL - DGE25-LO-DURBAL


<https://www.123roulement.be/roulement-palier/rotule/geg/dge25-lo-durbal>

### GE25-LO



**Description:** spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

**Outer ring:**  
bearing steel, hardened, ground and phosphated, single split in axial direction

**Lubrication:**  
lubrication required

order number	measurement [mm]				
	d	B	C	d <sub>1</sub> min	D
GE 25 LO	25	25	16	30,0	42

type	measurement [mm]			d <sub>1</sub>	α [°]	load rating C <sub>10</sub> [N]	weight [kg]
	r <sub>15</sub> min	r <sub>25</sub> min	d <sub>2</sub>				
GE 25 LO	0,6	0,6	35,5	4	240	0,120	

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952506401
Diam. intérieur	25 mm
Diam. extérieur	42 mm
Epaisseur	16 mm
Type	GEG
Poids	120 g
Lubrification	avec
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE