

Rotule GEG GE80-LO-DURBAL - GE80-LO-DURBAL


<https://www.123roulement.be/roulement-palier/rotule/geg/ge80-lo-durbal>

GE80-LO



Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

Outer ring:
bearing steel, hardened, ground and phosphated, single split in axial direction

Lubrication:
lubrication required

order number	measurement [mm]				
GE 80 LO	d	B	C	d ₂ min	D
	80	80	45	91,0	120

type	measurement [mm]		d ₂	α [°]	load rating C ₁₀ [kN]	weight [kg]
	r ₁₅ min	r ₂₅ min				
GE 80 LO	1,0	1,0	105,0	4	2000	2,400

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952506562
Diam. intérieur	80 mm
Diam. intérieur	3.15" inch
Diam. extérieur	120 mm
Diam. extérieur	4.724" inch
Epaisseur	45 mm
Epaisseur	1.772" inch
Type	GEG
Poids	2400 g
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE