

Rotule SA

BRTM30-00-502-DURBAL - BRTM30-00-502-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/brtm30-00-502-durbal>

BRTM30-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, trial of Cr-VI


inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]										
type	type hard chrome, left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	b ₁	b ₂				
BRTM 30 -00	-502	30	M 30 x 2	34,5	70		37	25				
measurements [mm]		weight		rotational speed limit		basic load rating		stat.				
type	h	l	b ₃	α	[°]	[kg]	n _{max}	d _{ym}	C	C ₀	[N]	[N]
BRTM 30	110	66	35	7,5		0,912	450	32500	24850			

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952506814
Diam. intérieur	30 mm
Diam. extérieur	70 mm
Epaisseur	37 mm
Type	SA
Poids	912 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE