

Rotule SI

BRTF16-03-501-DURBAL - BRTF16-03-501-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/brtf16-03-501-durbal>

BRTF16-03-501



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium complex soap grease, temperature range -45 °C to +120 °C, approval according to USDA H1



lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]									
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	h ₁	h ₂
BRTF 16 -03	-501		16	22,0	M 16	19,0	42	27	21	15	
		measurements [mm]					weight	rotational speed limit	basic load rating		
type	h	l	l ₁	l ₂	SW	α [°]	[kg]	n _{max} [min ⁻¹]	C [N]	stat. C ₀ [N]	
BRTF 16	64	28	8,0	22	22	7,0	0,220	975	13300	8900	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952506852
Diam. intérieur	16 mm
Diam. extérieur	42 mm
Epaisseur	21 mm
Type	SI
Poids	220 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE