

# Rotule GE

## BRTF20-00-501-DURBAL - BRTF20-00-501-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/ge/brtf20-00-501-durbal>

### BRTF20-00-501



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1



**lubrication fitting:**  
DIN 71 412 H1

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning roller bearing**

**female thread:**  
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]																				
type	right hand thread	left hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	d <sub>7</sub>	h <sub>1</sub>	h <sub>2</sub>	h	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	SW	α [°]	weight [kg]	rotational speed limit n <sub>max</sub> [min <sup>-1</sup> ]	basic load rating C [N]	stat. rating C <sub>0</sub> [N]	
BRTF 20 -00	-501		20	27,5	M 20 x 1,5	24,5	50	34	25	18												
BRTF 20			77	33	10,0	26	30	7,0	0,361	825	17000	11700										

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3616060468185
Diam. intérieur	20 mm
Diam. extérieur	50 mm
Epaisseur	25 mm
Type	GE
Poids	361 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE