


Rotule SA BRM25-00-501-DURBAL - BRM25-00-501-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/brm25-00-501-durbal>

BRM25-00-501



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, forged G V1

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex-soap-grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 2425 D11A (sizes 6 to 10)
DIN 21 412 H1 (sizes 12 to 30)

bearing clearance:
10 - 30 µm radial
tolerances:
see page 10

order number		measurements [mm]								
Type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	b ₁	b ₂	h
BRM 25 -00 -501			25	M 24 x 2	29,5	64	31	22,0	94	
measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating		
Type	l	l ₃	α [°]	[kg]	Y	v ₀	C [N]	C ₁₀ [N]	stat. C ₁₀ [N]	
BRM 25	57	30	5,0	0,602	2,02	2,12	600	11030	5680	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507118
Diam. intérieur	25 mm
Diam. extérieur	64 mm
Epaisseur	31 mm
Type	SA
Poids	602 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE