


Rotule SI BRF20-00-501-DURBAL - BRF20-00-501-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/brf20-00-501-durbal>

BRF20-00-501



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI.

inner ring:
ball bearing steel, hardened, superfinished.

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 30)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K



order number		measurements [mm]										
type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	h		
BRF 20 -00	-501	20	27,5	M 20 x 1,5	24,5	50	34	25	18,0	77		
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating		stat.		
type	l	l ₁	l ₂	SW	α [°]	β [g]	Y	v ₀	C	C ₀	C ₁₀	
BRF 20	33	10,0	26	30	7,0	0,367	2,46	2,58	825	7900	3450	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507293
Diam. intérieur	20 mm
Diam. intérieur	0.787" inch
Diam. extérieur	50 mm
Diam. extérieur	1.969" inch
Epaisseur	25 mm
Epaisseur	0.984" inch
Type	SI
Poids	367 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE