

Rotule SI

BRF22-00-501-DURBAL - BRF22-00-501-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/brf22-00-501-durbal>

BRF22-00-501



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI.

inner ring:
ball bearing steel, hardened, superfinished.

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1



lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 30)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]																	
type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	h	weight				calculation factors		rotational speed limit	basic load rating	
type	type	l	l ₁	l ₂	SW	α [°]	β [°]	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀	C ₁₀	C ₅₀	C ₁₀₀	C ₂₀₀	C ₅₀₀	C ₁₀₀₀	
BRF 22 -00 -501		22	30,0	M 22 x 1,5	26,0	54	38	28	20,0	84									
BRF 22		37	12,0	26	32	8,0	0,480	2,35	2,24	725	9300	3980							

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507309
Diam. intérieur	22 mm
Diam. extérieur	54 mm
Épaisseur	28 mm
Type	SI
Poids	480 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE