

Rotule SI

PF10-00-502-DURBAL - PF10-00-502-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/pf10-00-502-durbal>

PF10-00-502



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3485 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

female thread:
long-term lubrication, low maintenance, shields

order number		measurements [mm]											
type	type load shield	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂				
PF 10-00	-502	10	15	M 8	13,0	30	13,0	9					
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating		stat.			
type	h	l	l ₁	r	SW	α	[°]	[kg]	Y	%	n _{max} [rpm]	C [N]	C ₀ [N]
PF 10	38	17	14,5	10	13	7,0	0,063	1,90	1,81		1225	2605	985

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507378
Diam. intérieur	10 mm
Diam. extérieur	30 mm
Épaisseur	13 mm
Type	SI
Poids	63 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE