

Rotule SA

PM06-00-502-DURBAL - PM06-00-502-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/pm06-00-502-durbal>

PM06-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					weight			rotational speed limit			basic load rating		
type	approx. weight	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀ [N]
PM 06 -00	-502	6	M 10 x 1		8,5	24	14	14	10				1300	2445	765

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507477
Diam. intérieur	6 mm
Diam. extérieur	24 mm
Épaisseur	14 mm
Type	SA
Poids	62 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE