

Rotule SA PM08-02-502-DURBAL - PM08-02-502-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/pm08-02-502-durbal>


PM08-02-502



male thread:
long-term
lubrication,
low maintenance,
shields



**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**



rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating			
type	specification	d ₁	d ₂	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	Y	Y ₀	C	C ₀
PM 08-02	-502	8	M 12 x 1.5	11,0	30	17	15	10					
type		l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]				
PM 08	23	20	48,5	2,0	2,5	8,5	0,088	1,9	1,81	1225	2605	985	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507521
Diam. intérieur	8 mm
Diam. extérieur	30 mm
Épaisseur	15 mm
Type	SA
Poids	88 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE