

Rotule SA PM15-02-501-DURBAL - PM15-02-501-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/pm15-02-501-durbal>

PM15-02-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]				weight		calculation factors		rotational speed limit		basic load rating	
type	spiral thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀	C ₀ [N]
PM 15 -02	-501	15	M 20 x 1.5	18.5	42	26	20	14								
measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating								
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'	[kg]	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀	C ₀ [N]
PM 15	36	30	73.5	3.0	2.5	6.5				0.273	2.07	2.17	975	5485	3270	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507651
Diam. intérieur	15 mm
Diam. intérieur	0.591" inch
Diam. extérieur	42 mm
Diam. extérieur	1.654" inch
Epaisseur	20 mm
Epaisseur	0.787" inch
Type	SA
Poids	273 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE