

Rotule SA
PM17-00-502-DURBAL - PM17-00-502-DURBAL
<https://www.123roulement.be/roulement-palier/rotule/sa/pm17-00-502-durbal>


PM17-00-502



male thread:
long-term
lubrication,
low maintenance,
shields



**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**



rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-V5

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range -45 °C to +120 °C,
approval according to ISOA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]	
type	type	d1	d2
PM 17 -00	-502	17	M 20 x 1,5
		d3	d4
		21,0	48
		d5	d6
		25	22
		d7	d8
		16	16
measurements [mm]		weight	calculation factors
type	type	Y	Yc
PM 17	PM 17	0,401	2,35 2,46

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507675
Diam. intérieur	17 mm
Diam. extérieur	48 mm
Epaisseur	22 mm
Type	-
Poids	401 g
Filetage	-
Lubrification	-
Conditionnement	-

contact@123roulement.be
02 808 18 02
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE