

# Rotule SA PM17-01-502-DURBAL - PM17-01-502-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/pm17-01-502-durbal>

## PM17-01-502



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating					
type	specification	d <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>7</sub>	b <sub>1</sub>	b <sub>2</sub>	Y	Y <sub>0</sub>	C	C <sub>0</sub>			
PM 17 -01	-502	17	M 20 x 1,5	21,0	48	25	22	16							
measurements [mm]		weight		rotational speed limit		basic load rating									
type	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	u	z	α	α'	weight [kg]	Y	Y <sub>0</sub>	r <sub>max</sub> [mm]	C [N]	C <sub>0</sub> [N]
PM 17	36	36	78,5	3,5	2,5	7,0	0,354	2,35	2,46	875	5575	2680			

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507682
Diam. intérieur	17 mm
Diam. extérieur	48 mm
Epaisseur	22 mm
Type	SA
Poids	354 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE