

Rotule SA PM20-02-501-DURBAL - PM20-02-501-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/pm20-02-501-durbal>

PM20-02-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]		
type	approx. weight [kg]	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃
PM 20 -02 -501		20	M 24 x 1,5	24,0	56	30	24	18		

measurements [mm]		weight	calculation factors		rotational speed limit	basic load rating	
type	l ₁ l ₂ l ₃ h ₁ h ₂ u z	[kg]	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀ [N]
PM 20	41 88,5 3,5 3,0 5,5	0,519	2,76	2,90	775	6165	3140

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507736
Diam. intérieur	20 mm
Diam. extérieur	56 mm
Épaisseur	24 mm
Type	SA
Poids	519 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE