

## Rotule SI

### BRF06-60-502-DURBAL - BRF06-60-502-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/brf06-60-502-durbal>

BRF06-60-502



**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel**

**rod end housing:** stainless steel 1.4534, hardened, bearing race superfinished

**inner ring:** stainless steel, hardened, surface superfinished

**lubrication:** aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:** DIN 3405 D1/A (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

**bearing clearance:** 10 - 30 µm radial

**tolerances:** see page 10

**female thread:** long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]										
type	light load	medium load	high load	SW	α [°]	weight [kg]	calculation-factor Y	rotational speed limit v <sub>max</sub> [min <sup>-1</sup> ]	basic load rating C <sub>r</sub> [N]	stat. C <sub>r</sub> [N]	SW	α [°]
BRF 06 -60	-502	6	10,0	M 6	9,0	20	13	9	6,75	30		
BRF 06		12	5,0	10	11	8,0	0,024	2,09	2,19	1350	1900	450

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952509211
Diam. intérieur	6 mm
Diam. extérieur	20 mm
Epaisseur	9 mm
Type	SI
Poids	24 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE