

# Rotule SI

## BRF20-60-502-DURBAL - BRF20-60-502-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/brf20-60-502-durbal>

### BRF20-60-502



**rod end housing:**  
stainless steel 1.4534, hardened, bearing race superfinished

**inner ring:**  
stainless steel, hardened, surface superfinished

**lubrication:**  
aluminum-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1


**lubrication fitting:**  
DIN 3405 D1/A (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel**

**female thread:**  
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K



order number	type	measurements [mm]	weight	calculation-factors	rotational speed limit	basic load rating			
type	l <sub>1</sub>	l <sub>2</sub>	SW	α [°]	Y	v <sub>0</sub> [min]	C [N]	C <sub>0</sub> [N]	
BRF 20 -60 -502		20 27,5	M 20 x 1,5	24,5	50	34	25	18,0	77
BRF 20	33	10,0 26	30	7,0	0,367	2,46	2,58	825	5350 2300

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952509303
Diam. intérieur	20 mm
Diam. extérieur	50 mm
Epaisseur	25 mm
Type	SI
Poids	367 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE