


Rotule SI

BRF3-8-00-502-DURBAL - BRF3-8-00-502-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/brf3-8-00-502-durbal>

BRF3/8-00-502 

rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished


lubrication:
aluminum complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 1/4 and 3/8)
DIN 71 412 H1 (sizes 1/2 and 1 1/4)


bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing



female thread:
long-term lubrication, low maintenance, shields, dimensions in inches



order number		measurements [inches]										
type	right hand thread	d1	d2	d3	d4	d5	d6	d7	b1	b2	b3	
BRF 3/8 -00	-502	.375	.590	.3750-24 UNF	.468	1.102	.748	.551	.413			
measurements [inches]		weight		calculation factors		rotational speed limit		basic load rating		stat.		
type	h	l	l1	l2	SW	α [°]	Y	Y2	Trmax [mm]	C [N]	C0 [N]	
BRF 3/8	1.712	.787	.299	.590	.669	8.0	0,072	1,87	1,83	1225	4360	1425

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952510125
Diam. intérieur	9.53 mm
Diam. extérieur	27.99 mm
Épaisseur	14 mm
Type	SI
Poids	72 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE