


# Rotule SI

## BRF1-2-00-501-DURBAL - BRF1-2-00-501-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/brf1-2-00-501-durbal>

**BRF1/2-00-501** 

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

**inner ring:**  
ball bearing steel, hardened, superfinished


**lubrication:**  
aluminum complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3405 D1/A (sizes 1/4 and 3/8)  
DIN 71 412 H1 (sizes 1/2 and 1 1/4)


**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**



**female thread:**  
long-term lubrication, low maintenance, shields, dimensions in inches



order number		measurements [inches]										
type	right hand thread	left hand thread	d1	d2	d3	d4	d5	d6	d7	b1	b2	b3
BRF 1/2 -00	-501		500	.748	5000-20 UNF	574	1.311	.874	.624	.472		
measurements [inches]		weight	calculation factors	rotational speed limit	basic load rating							
type	h	l	l1	l2	SW	α [°]	Y	%	rpm	C	C0	
BRF 1/2	2.145	1.102	.279	.649	.757	7.5	0,127	1,74	1,82	1125	4850	1850

### CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952510149
Diam. intérieur	12.7 mm
Diam. extérieur	33.3 mm
Épaisseur	15.85 mm
Type	SI
Poids	127 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE