

Rotule SA BRM1-4-00-502-DURBAL - BRM1-4-00-502-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/brm1-4-00-502-durbal>

BRM1/4-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
dimensions in inches

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI


inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3425 D1/A (sizes 1/4 and 3/8)
DIN 71 412 H1 (sizes 1/2 and 1/1)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [inches]								
type	right hand thread, left hand thread	d ₁	d ₂ class 2	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂	b ₃
BRM 1/4 -00	-502	.250	2500-28 UNF	.356	.787	.354	.265			
measurements [inches]		weight		calculation factors		rotational speed limit		basic load rating		stat.
type	h	l	l ₃	α [°]	Y	Y ₂	n _{max} [min ⁻¹]	C [N]	C ₀ [N]	C ₁₀ [N]
BRM 1/4	1.437	.866	.551	8.0	0,022	2,09	2,19	1350	2670	645

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952510255
Diam. intérieur	6.35 mm
Diam. extérieur	19.99 mm
Epaisseur	8.99 mm
Type	SA
Poids	22 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE