

Roue libre FCS-6-NADELLA - FCS-6-NADELLA

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/roue/fcs-6-nadella>

Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F _z mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min	Suitable needle bush
6	FCS-6	6	10	12	2.15	22000	HK0608

Shaft Ø mm	Gapping			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Max. mm	Min. mm	Max. mm	Min. mm	
6	9.984	5.980	6.004	14	6.000	5.995	9.993	9.984	0.003

CARACTÉRISTIQUES PRODUIT

Marque	NADELLA
N° Ean13	3663952529370
Diam. intérieur	6 mm
Diam. extérieur	10 mm
Épaisseur	12 mm
Poids	3 g
Conditionnement	-
Norme	Sans norme

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE