

Roulement autre


AXNBT50115-NADELLA - AXNBT50115-NADELLA

<https://www.123roulement.be/roulement-palier/roulement-autre/axnbt50115-nadella>

Precision combined bearings,
with adjustable axial preload



AXNBT and ARNBT
series



- 1) 6% of dynamic axial load
- 2) with axial load equal to preload
- 3) rigidity of a single thrust bearing with load equal to preload
- 4) hexagon socket shallow head cap screw DIN 91

| Shaft Ø mm | Designation | | | d mm | D mm | F _a mm | D _A mm | D _m mm | B mm | C mm | B ₂ mm | r mm | r ₁ mm | Screw TCE II class 12.9 | Mounting | | | Torque Nm |
|------------------|-------------|-------------------|-------------------|---------|---------|----------------------|----------------------|----------------------|---------|---------|----------------------|---------|----------------------|-------------------------------|------------|---------|---------|--------------|
| | AXNBT | ARNBT series 1 | ARNBT series 2 | | | | | | | | | | | | N° viti | E mm | s mm | |
| 50 | 50 115 | | | 50 | 115 | 55 | 78 | 65.5 | 54 | 25 | 14.5 | 1.30 | 0.85 | 6x30 | 12 | 94 | 16 | 24 |

| Load Ratings kN | | | | Speed rating min ⁻¹ | Preload 1) N | Rotation 2) torque Nmm | Rigidity K to N/mm | Weight kg | Designation |
|-----------------|----------|--------|----------|-----------------------------------|-----------------|------------------------------|-----------------------|--------------|--------------|
| radial | | axial | | | | | | | |
| Dyn. C | Stat. Co | Dyn. C | Stat. Co | | | | | | |
| 44.0 | 96.0 | 28.5 | 104.0 | 3 800 | 1 680 | 650 | 3 500 | 1.932 | AXNBT 50 115 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | NADELLA |
| N° Ean13 | 3663952530901 |
| Diam. intérieur | 50 mm |
| Diam. extérieur | 78 mm |
| Épaisseur | 54 mm |
| Poids | 1932 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE