


Douille à aiguilles SJ7355-SS-RBC - SJ7355-SS-RBC

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/sj7355-ss-rbc>

Precision Ground Heavy Duty Needle Roller Bearings with Seals 



TYPE-SR
Outside seal with bearing lip
turned outward in
bearing # SJ - SS

| BEARING PART NUMBER | Fw Inside Diameter | | | B Outside Diameter | | B Width | A Housing Fillet Max. | Approx. Weight (lbs.) | Housing Shoulder Dia. 45-100" | Dynamic Capacity C (lbs.) | Static Capacity Co (lbs.) |
|---------------------|--------------------|--------|--------|--------------------|--------|---------|-----------------------|-----------------------|-------------------------------|---------------------------|---------------------------|
| | Nominal | Min. | Max. | Max. | Min. | | | | | | |
| SJ 7355 SS | 2 | 2.3011 | 2.3020 | 2.5605 | 2.5619 | 1.250 | .08 | .252 | 2.176 | 13,729 | 22,500 |

| Limits Speed (rpm) | Recommended Shaft Diameter | | | | Recommended Housing Bore | | | | BEARING PART NUMBER | | |
|--------------------|-------------------------------|--------|-------------------------------|--------|--------------------------|--------|------------------|--------|---------------------|--------|------------|
| | ISO H6, use with H7 h9 g8 fit | | ISO R6, use with N7 h9 g8 fit | | Slip Fit ISO H7 | | Press Fit ISO N7 | | | | |
| | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Max. | |
| 1,300 | 2.0500 | 1.9993 | 1.9998 | 1.9981 | 2.5025 | 2.5619 | .0008L | 2.5616 | 2.5621 | .0006F | SJ 7355 SS |

All dimensions in inches.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | RBC |
| N° Ean13 | 3663952531632 |
| Diam. intérieur | 50.8 mm |
| Diam. extérieur | 65.088 mm |
| Épaisseur | 31.75 mm |
| Poids | 255 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE