

## Roulement à bille simple rangée 3003-SS-NICE - 3003-SS-NICE

<https://www.123roulement.be/roulement-palier/roulement-bille/simple-rangee/3003-ss-nice>

**3000 Series® Semi-Ground Radial Bearings** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3003™				SS		+0.005 +0.13 -0.000 -0.013	+0.000 +0.00 -0.005 -0.013

WIDTH B (in) (mm)	BASIC LOAD RATINGS		WEIGHT W (lb) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)		da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.2813 7.1450	325 1446	255 1135	0.03 0.01	0.474 12.04	0.778 19.76	0.012 0.30

Width for sealed versions = 0.3438 (8.733)   
 Weights given are for greased and sealed versions   
 3038 and larger +0.0005/-0.005 (+0.001/-0.125)

## CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558080
Diam. intérieur	7.938 mm
Diam. extérieur	22.225 mm
Épaisseur	7.145 mm
Poids	10 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE