

Roulement à bille simple rangée 3004-SC-NICE - 3004-SC-NICE

<https://www.123roulement.be/roulement-palier/roulement-bille/simple-rangee/3004-sc-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|---------|-------------|-------------|---------------|---------------|------|------------------------------------|-------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3004™ | | SC | | | | +0.005 +0.13 -0.000 -0.00 | +0.000 +0.00 -0.015 -0.015 |
| | | | | | | 9.525 | 22.225 |

| WIDTH B (in) (mm) | BASIC LOAD RATINGS | | WEIGHT W (lb) (kg) | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|------------------------------|------------------------------|-----------------------------|--------------------------------|------------------------|-----------------------|
| | DYNAMIC C (lbs) (N) | STATIC Co (lbs) (N) | | da min (in) (mm) | Da max (in) (mm) | r max (in) (mm) |
| 0.2813 7.1450 | 325 1448 | 250 1135 | 0.03 0.01 | 0.474 12.04 | 0.778 19.76 | 0.015 0.38 |

Width for sealed versions = 0.3438 (8.733) Weights given are for greased and sealed versions
3038 and larger +0.000/-0.006 (+0.00/-0.15)

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | NICE |
| N° Ean13 | 3663952558134 |
| Diam. intérieur | 9.525 mm |
| Diam. extérieur | 22.225 mm |
| Épaisseur | 7.145 mm |
| Poids | 10 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE